

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** CIMGUARD® 10  
CORROSION PREVENTIVE

**Other means of identification**

**SDS number** Not applicable

**Recommended use** CORROSION PREVENTIVE

**Recommended restrictions** None known.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

**Company name** CIMCOOL® Industrial Products LLC  
3000 Disney Street  
Cincinnati, Ohio 45209

**Telephone (General Information)** 513-458-8100

**Emergency telephone number** 1-800-424-9300 (CHEMTREC)

**Emergency telephone number (outside USA)** 1-703-527-3887 (CHEMTREC)

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 2
<b>Health hazards</b>	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
<b>OSHA defined hazards</b>	Not classified.	

#### Label elements



**Signal word**

Danger

**Hazard statement**

Flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

<b>Response</b>	If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.
<b>Storage</b>	Store in accordance with local/regional/national/international regulation. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from incompatible materials.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		64742-47-8	10 - 30
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.		64742-88-7	10 - 30
PROPANE		74-98-6	5 - 10
DIETHYLENE GLYCOL MONOBUTYL ETHER		112-34-5	1 - 5
ISOBUTANE		75-28-5	1 - 5
Other components below reportable levels			10 - 30

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
<b>Skin contact</b>	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
<b>General information</b>	If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Water fog. Dry chemicals. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Wear suitable protective equipment.
<b>Fire fighting equipment/instructions</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Flammable aerosol.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Local authorities should be advised if significant spillages cannot be contained. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

### Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

### Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. To maintain product quality, do not store in heat or direct sunlight. Store in a well-ventilated place. Do not allow material to freeze. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### U.S. - OSHA

	Type	Value
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS 64742-88-7)	TWA	2000 mg/m3
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)	TWA	500 ppm

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	Type	Value
PROPANE (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

	Type	Value
ISOBUTANE (CAS 75-28-5)	TWA	1900 mg/m3
PROPANE (CAS 74-98-6)	TWA	1800 mg/m3
ISOBUTANE (CAS 75-28-5)	TWA	800 ppm
PROPANE (CAS 74-98-6)	TWA	1000 ppm

#### ACGIH

	Type	Value	Form
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS 64742-88-7)	TWA	200 mg/m3	Vapor.

**ACGIH**

	Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)	TWA	200 mg/m3	Vapor.

**US. ACGIH Threshold Limit Values**

	Type	Value	Form
ISOBUTANE (CAS 75-28-5)	STEL	1000 ppm	
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.

**Skin protection****Hand protection**

Use protective gloves made of: Nitrile.

**Other**

Wear suitable protective clothing and gloves.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

CLEAR

**Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Not available.

**Odor**

CHEMICAL

**Odor threshold**

Not available.

**pH**

Not Applicable

**Melting point/freezing point**

Not Applicable

**Initial boiling point and boiling range**

> 355 °F (> 179.44 °C) (liquid) estimated

**Flash point**

< 153 °F (< 67.2 °C) Setaflash (liquid) estimated

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not applicable.

**Upper/lower flammability or explosive limits****Flammability limit - lower (%)**

Not available.

**Flammability limit - upper (%)**

Not available.

**Explosive limit - lower (%)**

Not available.

**Explosive limit - upper (%)**

Not available.

**Vapor pressure**

Not available.

**Vapor density**

Not available.

**Relative density**

Not available.

<b>Solubility(ies)</b>	Insoluble
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Specific gravity</b>	0.84 (liquid)
<b>VOC ASTM D2369</b>	76 % (liquid)

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Acids. Avoid contact with oxidizers or reducing agents. Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines.
<b>Hazardous decomposition products</b>	Smoke, fumes, oxides of nitrogen, and oxides of carbon

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
---	--

### Information on toxicological effects

<b>Acute toxicity</b>	May be fatal if swallowed and enters airways. Harmful if inhaled. Narcotic effects. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.
-----------------------	---

Components	Species	Test Results
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	2700 mg/kg
<i>Oral</i>		
LD50	Guinea pig	2000 mg/kg
	Mouse	2400 mg/kg
	Rabbit	2200 mg/kg
	Rat	3305 mg/kg
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
ISOBUTANE (CAS 75-28-5)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	52 mg/l, 1 Hours
	Rat	658 mg/l, 4 hours
PROPANE (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes 658 mg/l, 4 hours
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS 64742-88-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5.28 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
TRIETHANOLAMINE (CAS 102-71-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Oral</i>		
LD50	Guinea pig	5300 mg/kg
	Rat	8 g/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation. Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
TRIETHANOLAMINE (CAS 102-71-6)	3 Not classifiable as to carcinogenicity to humans.
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not listed.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

## 12. Ecological information

<b>Ecotoxicity</b>	Very toxic to aquatic life with long lasting effects.
--------------------	---

Components	Species		Test Results
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia	> 100 mg/l, 48 hours
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	1300 mg/l, 96 hours
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> )	2.9 mg/l, 96 hours
<i>Acute</i>			
Crustacea	EC50	Daphnia	1.4 mg/l, 48 hours
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS 64742-88-7)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia	1.4 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> )	2 mg/l, 96 hours
TRIETHANOLAMINE (CAS 102-71-6)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Ceriodaphnia dubia</i> )	565.2 - 658.3 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	10610 - 13010 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

DIETHYLENE GLYCOL MONOBUTYL ETHER	1
ISOBUTANE	2.76
PROPANE	2.36
TRIETHANOLAMINE	-1

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

**DOT**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, (each not exceeding 1 L capacity)
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-



<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed.
<b>Cargo aircraft only</b>	Allowed.

Supplemental Information: Air shipment is not allowed for this product when packaged in Case lot quantity. Case lot quantity packaging does not meet requirements of "IATA Dangerous Goods Regulations, Section 6 Packaging Specifications and Performance Tests" for this mode of transport.

#### IMDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	
<b>Class</b>	2
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not established.

#### DOT





## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

Yes

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
DIETHYLENE GLYCOL MONOBUTYL ETHER	112-34-5	1 - 5

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

ISOBUTANE (CAS 75-28-5)  
 PROPANE (CAS 74-98-6)

#### Safe Drinking Water Act (SDWA)

Not regulated.

#### Food and Drug Administration (FDA)

Not regulated.

### US state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

#### US. Massachusetts RTK - Substance List

ISOBUTANE (CAS 75-28-5)  
 PROPANE (CAS 74-98-6)  
 TRIETHANOLAMINE (CAS 102-71-6)

#### US. New Jersey Worker and Community Right-to-Know Act

ISOBUTANE (CAS 75-28-5)  
 PROPANE (CAS 74-98-6)  
 TRIETHANOLAMINE (CAS 102-71-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

ISOBUTANE (CAS 75-28-5)  
 PROPANE (CAS 74-98-6)  
 TRIETHANOLAMINE (CAS 102-71-6)

**US. Rhode Island RTK**

ISOBUTANE (CAS 75-28-5)  
 PROPANE (CAS 74-98-6)

**California South Coast Air  
 Quality Management  
 District (SCAQMD) Rule  
 1144 (VOC Emissions)**

This product is subject to SCAQMD Rule 1144; it is not compliant and shall not be sold and used in the SCAQMD. The VOC content of the product is 614 g/L, measured by ASTM Method E-1868-10. This product has a specified VOC limit of 50 g/L.

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**International Inventories**

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

**16. Other information, including date of preparation or last revision**

**Issue date** 06-23-2015

**Revision date** 07-06-2015

**Version #** 02

**Further information** Not available.

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Information** Physical & Chemical Properties: Multiple Properties