

SAFETY DATA SHEET

1. Identification

Product identifier	CIMSTAR® QUAL STAR® LFZ METALWORKING FLUID	
Other means of identification		
SDS number	Not applicable	
Recommended use	METALWORKING FLUID	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	CIMCOOL® Industrial Products LLC 3000 Disney Street Cincinnati, Ohio 45209	
Telephone (General Information)	513-458-8199	
Emergency telephone number	1-800-424-9300 (CHEMTREC)	
Emergency telephone number (outside USA)	1-703-527-3887 (CHEMTREC)	

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Acute toxicity, inhalation	Category 4
	Serious eye damage/eye irritation	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Warning	
Hazard statement	Causes serious eye irritation. Harmful if inhaled.	
Precautionary statement		
Prevention	Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.	
Response	IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash before reuse.	
Storage	Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Store away from incompatible materials. Store in accordance with local/regional/national regulations.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	10.77% of the mixture consists of component(s) of unknown acute inhalation toxicity.	

3. Composition/information on ingredients

Mixtures

Material name: CIMSTAR® QUAL STAR® LFZ
Version #: 01 Issue date: 02-17-2015

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	10 - 30
HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S- TRIAZINE		4719-04-4	1 - 5
MONOETHANOLAMINE		141-43-5	1 - 5
NONYLPHENOXYPOLYETHOXYE THANOL		127087-87-0	1 - 5
Other components below reportable levels			40 - 70

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms are experienced, remove source of contamination or move victim to fresh air. Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly. Do not induce vomiting. Drink 1 or 2 glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Not applicable, non-combustible.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. Move container from fire area if it can be done without risk.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Prevent product from entering drains. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Do not flush spill to drain. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not ingest. Do not breathe mist or vapor. Do not get this material on clothing. Avoid contact with skin and eyes. Avoid prolonged and repeated contact. Use only in well-ventilated areas. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Wash contaminated clothing before reuse. Practice good housekeeping. Handle and open container with care. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

To maintain product quality, do not store in heat or direct sunlight. Use care in handling/storage. Keep containers closed when not in use. Keep away from food, drink and animal feedingstuffs. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Store in a well-ventilated place. Room temperature - normal conditions. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	PEL	5 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	Type	Value
MONOETHANOLAMINE (CAS 141-43-5)	PEL	6 mg/m3 3 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

	Type	Value
MONOETHANOLAMINE (CAS 141-43-5)	STEL	15 mg/m3
	TWA	6 ppm
2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8)	TWA	8 mg/m3
MONOETHANOLAMINE (CAS 141-43-5)	TWA	14 mg/m3
	TWA	3 ppm
2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8)	TWA	2 ppm

ACGIH

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	TWA	5 mg/m ³

US. ACGIH Threshold Limit Values

	Type	Value
MONOETHANOLAMINE (CAS 141-43-5)	STEL	6 ppm
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m ³
MONOETHANOLAMINE (CAS 141-43-5)	TWA	3 ppm
2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8)	TWA	0.5 ppm

Exposure guidelines**US - California OELs: Skin designation**

2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8) Skin designation applies.

US ACGIH Threshold Limit Values: Skin designation

2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8) Can be absorbed through the skin.

Appropriate engineering controls

Ensure compliance with applicable exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.

Skin protection

Hand protection Use protective gloves made of: Nitrile.

Other Wear suitable protective clothing and gloves.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	CLEAR
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	CHEMICAL
Odor threshold	Not available.
pH	9.7
Melting point/freezing point	< 26 °F (< -3.3 °C)
Initial boiling point and boiling range	> 212 °F (> 100 °C)
Flash point	Not Applicable
Evaporation rate	Like water when diluted

Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	100 % Water Miscible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
pH in aqueous solution	8.9 @ 5%
Specific gravity	1.013
VOC ASTM D2369	10 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines. Strong acids. Strong oxidizing agents. Avoid contact with oxidizers or reducing agents.
Hazardous decomposition products	Smoke, fumes, oxides of nitrogen, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause irritation to the respiratory system.
Skin contact	May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Causes serious eye irritation.
Ingestion	May be harmful if swallowed. Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin.

Information on toxicological effects

Acute toxicity Harmful if inhaled. May be harmful if swallowed. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components	Species	Test Results
2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	1680 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 0.41 mg/l, 4 hours

Components	Species	Test Results
<i>Oral</i> LD50	Rat	550 mg/kg
3-iodo-2-propynyl butylcarbamate (CAS 55406-53-6)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg
<i>Oral</i> LD50	Rat	1.1 g/kg
MONOETHANOLAMINE (CAS 141-43-5)		
Acute		
<i>Dermal</i> LD50	Rabbit	1025 mg/kg
<i>Inhalation</i> LC50	Mouse	> 1210 mg/m ³
<i>Oral</i> LD50	Guinea pig	620 mg/kg
	Mouse	700 mg/kg
	Rat	1515 mg/kg
NONYLPHENOXYPOLYETHOXYETHANOL (CAS 127087-87-0)		
Acute		
<i>Dermal</i> LD50	Rabbit	2573 mg/kg
<i>Oral</i> LD50	Rat	5000 mg/kg
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 5000 mg/kg
<i>Inhalation</i> LC50	Rat	2.18 mg/l, 4 hours
<i>Oral</i> LD50	Rat	> 5000 mg/kg
TRIETHANOLAMINE (CAS 102-71-6)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg
<i>Oral</i> LD50	Guinea pig	5300 mg/kg
	Rat	8 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not classified.
Skin sensitization	Not classified.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6)

3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be harmful if swallowed and enters airways.
Chronic effects	Prolonged exposure may cause chronic effects.
Further information	Symptoms may be delayed.

12. Ecological information**Ecotoxicity** Contains a substance which causes risk of hazardous effects to the environment.

Components	Species	Test Results
2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 62.6 - 91.2 mg/l, 48 hours
<i>Acute</i>		
Fish	LC50	Ide, silver or golden orfe (Leuciscus idus) 32 mg/l, 96 hours
3-IODO-2-PROPYNYL BUTYLCARBAMATE (CAS 55406-53-6)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 0.05 - 0.089 mg/l, 96 hours
MONOETHANOLAMINE (CAS 141-43-5)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 114 - 196 mg/l, 96 hours
NONYLPHENOXYPOLYETHOXYETHANOL (CAS 127087-87-0)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia 1.6 - 10 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 1.2 - 9.3 mg/l, 96 hours
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia > 1000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) > 30000 mg/l, 96 hours
TRIETHANOLAMINE (CAS 102-71-6)		
Aquatic		
Crustacea	EC50	Water flea (Ceriodaphnia dubia) 565.2 - 658.3 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 10610 - 13010 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

2-N-DIBUTYLAMINOETHANOL	1.86, @ 20°C
	2.33
MONOETHANOLAMINE	-1.31
TRIETHANOLAMINE	-1

Mobility in soil This product is miscible in water.
Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations Dispose in accordance with all applicable regulations.
Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT
Not regulated as dangerous goods.

IATA
Not regulated as dangerous goods.

IMDG
Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S-TRIAZINE (CAS 4719-04-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
3-IODO-2-PROPYNYL BUTYLCARBAMATE	55406-53-6	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**Food and Drug Administration (FDA)** Not regulated.**US state regulations** Product is a hazardous substance as defined under the OSHA Hazard Communication Standard and may be reportable under the provisions of SARA Sections 311 and 312.**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. Massachusetts RTK - Substance List

2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8)

MONOETHANOLAMINE (CAS 141-43-5)

TRIETHANOLAMINE (CAS 102-71-6)

US. New Jersey Worker and Community Right-to-Know Act

2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8)

3-iodo-2-propynyl butylcarbamate (CAS 55406-53-6)

MONOETHANOLAMINE (CAS 141-43-5)

TRIETHANOLAMINE (CAS 102-71-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-N-DIBUTYLAMINOETHANOL (CAS 102-81-8)

MONOETHANOLAMINE (CAS 141-43-5)

TRIETHANOLAMINE (CAS 102-71-6)

US. Rhode Island RTK

3-iodo-2-propynyl butylcarbamate (CAS 55406-53-6)

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 53 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 100 % to maintain compliance.**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision**Issue date** 02-17-2015**Version #** 01**Further information** Not available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Product and Company Identification: Product and Company Identification
Hazards Identification: US Hazard Categories
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Transport Information: Proper Shipping Name/Packing Group
Regulatory Information: United States
Material Attributes & Uses; Experimental Data: Product Uses
HazReg Data: North America
GHS: Classification