SAFETY DATA SHEET



1. Identification

Product identifier MILFORM® 6670

STAMPING AND DRAWING FLUID

Other means of identification

SDS number Not applicable

STAMPING AND DRAWING FLUID Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CIMCOOL® Industrial Products LLC

> 3000 Disney Street Cincinnati, Ohio 45209

Telephone (General

Information)

513-458-8100

Emergency telephone

number

1-800-424-9300 (CHEMTREC)

Emergency telephone number (outside USA) 1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

> Category 2 Serious eye damage/eye irritation Sensitization, skin Category 1

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Avoid release to the environment.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical Response

advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. Take off contaminated clothing and

wash before reuse.

Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Store away **Storage**

from incompatible materials. Store in accordance with local/regional/national/international

regulation.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: MILFORM® 6670 SDS US

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
TRIETHANOLAMINE		102-71-6	7 - 13
DECANEDIOIC ACID		111-20-6	1 - 5
MONOETHANOLAMINE		141-43-5	0.5 - 1.5
HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S- TRIAZINE		4719-04-4	0.1 - 1
Other components below reportable leve	ls		60 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing Skin contact

and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if symptoms occur.

Rinse mouth thoroughly. Do not induce vomiting. Drink 1 or 2 glasses of water. If vomiting occurs, Ingestion

keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if

you feel unwell.

Most important

symptoms/effects, acute and

delayed

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Defatting of the skin. May cause allergic skin reaction.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

Not applicable, non-combustible.

media

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Wear suitable protective equipment.

Fire fighting

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. Move container from fire area if it can be done without risk

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: MILFORM® 6670 SDS US 2/8

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Prevent product from entering drains. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Do not flush spill to drain. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not ingest. Do not get this material on clothing. Avoid breathing mist or vapor. Avoid contact with skin and eyes. Avoid prolonged and repeated contact. Use only in well-ventilated areas. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Wash contaminated clothing before reuse. Practice good housekeeping. Handle and open container with care. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

To maintain product quality, do not store in heat or direct sunlight. Use care in handling/storage. Keep containers closed when not in use. Keep away from food, drink and animal feedingstuffs. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Store in a well-ventilated place. Room temperature - normal conditions. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	Туре	Value	
MONOETHANOLAMINE (CAS 141-43-5)	PEL	6 mg/m3	
		3 ppm	
US. NIOSH: Pocket Guide to Chemical Hazards			
	Туре	Value	
MONOETHANOLAMINE (CAS 141-43-5)	STEL	15 mg/m3	
		6 ppm	
	TWA	8 mg/m3	
		3 ppm	
US. ACGIH Threshold Limit Value	s		
	Туре	Value	
MONOETHANOLAMINE (CAS 141-43-5)	STEL	6 ppm	
TRIETHANOLÁMINE (CAS 102-71-6)	TWA	5 mg/m3	
MONOETHANOLAMINE (CAS 141-43-5)	TWA	3 ppm	

Appropriate engineering controls

Ensure compliance with applicable exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.

Material name: MILFORM® 6670 SDS US Skin protection

Use protective gloves made of: Nitrile. Hand protection

Other Wear suitable protective clothing and gloves.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

9. Physical and chemical properties

Appearance CLEAR Physical state Liquid. Liquid. **Form**

Not available. Color Chemical Odor **Odor threshold** Not available.

9.2 Ηq

Melting point/freezing point < 32 °F (< 0 °C) estimated

Initial boiling point and boiling

range

> 212 °F (> 100 °C)

Flash point Not Applicable

Evaporation rate Like water when diluted

Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Vapor pressure Not available. Vapor density Not available.

100 % Water Miscible Solubility(ies)

Partition coefficient

(n-octanol/water)

Relative density

Not available.

Not available.

Auto-ignition temperature Not available. Not available. **Decomposition temperature Viscosity** Not available.

Other information

pH in aqueous solution 8.8 @ 20% 1.078 Specific gravity 4 % **VOC ASTM D2369**

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

occur.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Acids. Avoid contact with oxidizers or reducing agents. Do not add sodium nitrite or other

nitrosating agents which may form cancer causing nitrosamines.

Smoke, fumes, oxides of nitrogen, and oxides of carbon

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Health injuries are not known or expected under normal

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May be harmful if swallowed. Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Defatting of the skin. May cause an allergic

skin reaction.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction. May be harmful if swallowed. Expected to be a low hazard for

usual industrial or commercial handling by trained personnel.

Components	Species	Test Results		
DECANEDIOIC ACID (CAS 111-20-6)				
Acute				
Dermal				
LD50	Rabbit	1175 mg/kg		
Oral				
LC50	Rat	> 4500 mg/l		
LD50	Rat	2750 mg/kg		
MONOETHANOLAMINE (CAS 141-43-5)				
Acute				
Dermal				
LD50	Rabbit	1025 mg/kg		
Oral				
LD50	Guinea pig	620 mg/kg		
	Mouse	700 mg/kg		
	Rat	10.2 g/kg		
TRIETHANOLAMINE (CAS	S 102-71-6)			
Acute				
Dermal				
LD50	Rabbit	> 2000 mg/kg		
Oral				
LD50	Guinea pig	5300 mg/kg		
	Rat	8 g/kg		

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation. Prolonged skin contact may cause temporary irritation. Defatting, drying and

cracking of skin.

Serious eye damage/eye

irritation

Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Not classified. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

Material name: MILFORM® 6670 5/8

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

May be harmful if swallowed and enters airways. **Aspiration hazard** Prolonged exposure may cause chronic effects. **Chronic effects**

Symptoms may be delayed. **Further information**

12. Ecological information

Contains a substance which causes risk of hazardous effects to the environment. **Ecotoxicity**

Components		Species	Test Results
DECANEDIOIC ACID	(CAS 111-20-6)		
Aquatic			
Acute			
Crustacea	EC50	Daphnia	85.7 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	97 mg/l, 96 hours
MONOETHANOLAMIN	NE (CAS 141-43-5)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	114 - 196 mg/l, 96 hours
TRIETHANOLAMINE ((CAS 102-71-6)		
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	565.2 - 658.3 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	10610 - 13010 mg/l. 96 hours

^{*} Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

MONOETHANOLAMINE -1.31 **TRIETHANOLAMINE** _1

Mobility in soil This product is miscible in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with

chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

Not regulated as dangerous goods.

Material name: MILFORM® 6670 SDS US

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to No.

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311

and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S-

1.0 % One-Time Export Notification only.

TRIAZINE (CAS 4719-04-4)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

MONOETHANOLAMINE (CAS 141-43-5) TRIETHANOLAMINE (CAS 102-71-6)

US. New Jersey Worker and Community Right-to-Know Act

MONOETHANOLAMINE (CAS 141-43-5) TRIETHANOLAMINE (CAS 102-71-6)

US. Pennsylvania Worker and Community Right-to-Know Law

MONOETHANOLAMINE (CAS 141-43-5) TRIETHANOLAMINE (CAS 102-71-6)

US. Rhode Island RTK

Not regulated.

Material name: MILFORM® 6670 SDS US

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 0 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 100 % to maintain compliance.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 01-30-2015

 Revision date
 06-22-2015

Version # 02

Further information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision InformationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: MILFORM® 6670 SDS US