

SAFETY DATA SHEET

1. Identification

Product identifier OAK® 15C-FR
METALWORKING OIL

Other means of identification

SDS number Not applicable

Recommended use METALWORKING OIL

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name CIMCOOL® Industrial Products LLC
3000 Disney Street
Cincinnati, Ohio 45209

Telephone (General Information) 513-458-8100

Emergency telephone number 1-800-424-9300 (CHEMTREC)

Emergency telephone number (outside USA) 1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, inhalation Category 4
Skin irritation Category 2
Serious eye irritation Category 2A
Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Avoid breathing mist. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear protective gloves.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	60 - 70
NONYLPHENOXYPOLYETHOXYE THANOL		127087-87-0	1 - 3
Other components below reportable levels			30 - 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician or Poison Control Center immediately.
Skin contact	Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a physician or poison control center immediately.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause respiratory irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. The product is immiscible with water and will spread on the water surface. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	PEL	5 mg/m3

ACGIH

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	TWA	5 mg/m3

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.

Skin protection

Hand protection

Use protective gloves made of: Nitrile.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

CLEAR

Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	CHEMICAL
Odor threshold	Not available.
pH	Not Applicable
Melting point/freezing point	Not Determined
Initial boiling point and boiling range	Not Applicable
Flash point	275 °F (135 °C) Cleveland Open Cup
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Insoluble in Water
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	≤ 20.5 mm ² /s @ 40°C 20 cSt @ 100°F (38°C)
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.900
VOC ASTM D2369	15 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Oxidizing agents.
Hazardous decomposition products	Smoke, fumes, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled.
Skin contact	Causes skin irritation.
Eye contact	Causes eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components	Species	Test Results
------------	---------	--------------

NONYLPHENOXYPOLYETHOXYETHANOL (CAS 127087-87-0)

Acute

Dermal

Liquid

LD50	Rabbit	2573 mg/kg
------	--------	------------

Oral

Liquid

LD50	Rat	3980 mg/kg
------	-----	------------

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

Acute

Dermal

Liquid

LD50	Rabbit	> 2000 mg/kg
------	--------	--------------

Inhalation

Mist

LC50	Rat	2.18 mg/l, 4 hr
------	-----	-----------------

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Not classified.

Further information The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

12. Ecological information

Ecotoxicity Contains a substance which causes risk of hazardous effects to the environment.

Components	Species		Test Results
NONYLPHENOXYPOLYETHOXYETHANOL (CAS 127087-87-0)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	1.6 - 10 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	1.2 - 9.3 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

NONYLPHENOXYPOLYETHOXYETHANOL (CAS 127087-87-0)

Nonylphenol (NP) and Nonylphenol Ethoxylates (NPEs) Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - No
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes**SARA 313 (TRI reporting)**
Not regulated.**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**Food and Drug Administration (FDA)** Not regulated.**US state regulations****US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is not compliant and shall not be sold and used in the SCAQMD. The VOC content of the product is 131 g/L, measured by ASTM Method 1868-10. This product has a specified VOC limit of 75 g/L.**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date	07-08-2015
Revision date	06-23-2017
Version #	02
Further information	Not available.
NFPA ratings	Health: 1 Flammability: 1 Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.