

## 1. Identification

<b>Product identifier</b>	<b>OAK® 15C</b> METALWORKING OIL
<b>Other means of identification</b>	
<b>SDS number</b>	Not applicable
<b>Recommended use</b>	METALWORKING OIL
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufacturer</b>	
<b>Company name</b>	CIMCOOL® Industrial Products LLC 3000 Disney Street Cincinnati, Ohio 45209
<b>Telephone (General Information)</b>	513-458-8199
<b>Emergency telephone number</b>	1-800-424-9300 (CHEMTREC)
<b>Emergency telephone number (outside USA)</b>	1-703-527-3887 (CHEMTREC)

## 2. Hazard(s) identification

<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Acute toxicity, inhalation	Category 4
	Serious eye damage/eye irritation	Category 2
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		



<b>Signal word</b>	Warning
<b>Hazard statement</b>	Causes serious eye irritation. Harmful if inhaled.
<b>Precautionary statement</b>	
<b>Prevention</b>	Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.
<b>Response</b>	IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse.
<b>Storage</b>	Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Store away from incompatible materials. Store in accordance with local/regional/national/international regulations.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	1.54% of the mixture consists of component(s) of unknown acute inhalation toxicity. 1.35% of the mixture consists of component(s) of unknown acute dermal toxicity.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	60 - 100
SEVERELY HYDROTREATED NAPHTHENIC DISTILLATES		64742-53-6	10 - 30
Other components below reportable levels			1 - 5

The exact percentages of hazardous ingredients have been withheld as a trade secret.

#### 4. First-aid measures

<b>Inhalation</b>	If symptoms are experienced, remove source of contamination or move victim to fresh air. Get medical attention if symptoms persist.
<b>Skin contact</b>	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly. Do not induce vomiting. Do not give liquids. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
<b>General information</b>	Get medical attention if symptoms occur. Show this safety data sheet to the doctor in attendance.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemicals. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Wear suitable protective equipment.
<b>Fire-fighting equipment/instructions</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. Move container from fire area if it can be done without risk.
<b>General fire hazards</b>	Combustible liquid.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Local authorities should be advised if significant spillages cannot be contained. The product is immiscible with water and will spread on the water surface. Extinguish all flames in the vicinity.  Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Prevent product from entering drains. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. Do not flush spill to drain. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. Contact local authorities in case of spillage to drain/aquatic environment.

## 7. Handling and storage

### Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe vapor. Do not ingest. Do not get this material on clothing. Avoid contact with skin and eyes. Avoid prolonged and repeated contact. Use only in well-ventilated areas. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Wash contaminated clothing before reuse. Practice good housekeeping. Handle and open container with care. Do not empty into drains.

### Conditions for safe storage, including any incompatibilities

To maintain product quality, do not store in heat or direct sunlight. Use care in handling/storage. Keep containers closed when not in use. Keep this material away from food, drink and animal feed. Store in original container. Store away from incompatible materials (see Section 10 of the SDS). Do not allow material to freeze. Room temperature - normal conditions. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### U.S. - OSHA

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	PEL	5 mg/m3
SEVERELY HYDROTREATED NAPHTHENIC DISTILLATES (CAS 64742-53-6)	PEL	5 mg/m3

#### ACGIH

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	TWA	5 mg/m3
SEVERELY HYDROTREATED NAPHTHENIC DISTILLATES (CAS 64742-53-6)	TWA	5 mg/m3

### Appropriate engineering controls

Ensure compliance with applicable exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.

#### Skin protection

**Hand protection** Use protective gloves made of: Nitrile.

**Other** Wear suitable protective clothing and gloves.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

<b>Appearance</b>	CLEAR
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Not available.
<b>Odor</b>	CHEMICAL
<b>Odor threshold</b>	Not available.

<b>pH</b>	Not Applicable
<b>Melting point/freezing point</b>	< 32 °F (< 0 °C) estimated
<b>Initial boiling point and boiling range</b>	> 212 °F (> 100 °C) estimated
<b>Flash point</b>	275 °F (135 °C) Cleveland Open Cup
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Insoluble
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Flash point class</b>	Combustible IIIB
<b>Specific gravity</b>	0.9
<b>VOC ASTM D2369</b>	29 %

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents. Avoid contact with oxidizers or reducing agents.
<b>Hazardous decomposition products</b>	Smoke, fumes, and oxides of carbon

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	May be harmful if swallowed. Expected to be a low ingestion hazard.
<b>Inhalation</b>	Harmful if inhaled. May cause irritation to the respiratory system.
<b>Skin contact</b>	May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Eye contact</b>	Causes eye irritation.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin.
---	--

### Information on toxicological effects

<b>Acute toxicity</b>	Harmful if inhaled. May be harmful if swallowed. May be harmful in contact with skin.
-----------------------	---

Components	Species	Test Results
SEVERELY HYDROTREATED NAPHTHENIC DISTILLATES (CAS 64742-53-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg

Components	Species	Test Results
<i>Inhalation</i>		
LC50	Rat	2.18 mg/l, 4 hr
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

**Acute**

*Dermal*

LD50 Rabbit > 3000 mg/kg

*Inhalation*

LC50 Rat 2.18 mg/l, 4 hr

*Oral*

LD50 Rat > 5000 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.

**Serious eye damage/eye irritation** Causes eye irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not classified.

**Skin sensitization** Not classified.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** May be harmful if swallowed and enters airways.

**Chronic effects** Prolonged exposure may cause chronic effects.

**Further information** Symptoms may be delayed.

**12. Ecological information**

**Ecotoxicity** Contains a substance which causes risk of hazardous effects to the environment.

Components	Species	Test Results
SEVERELY HYDROTREATED NAPHTHENIC DISTILLATES (CAS 64742-53-6)		
<i>Acute</i>		
Fish	EC50	Fish > 100 mg/l
<i>Chronic</i>		
Fish	NOEC	Fish > 100 mg/l
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)		
<i>Acute</i>		
Fish	LC50	Fish > 100 mg/l
<i>Chronic</i>		
Fish	NOEC	Fish > 100 mg/l

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

<b>Disposal instructions</b>	Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not available.

### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded. All components are on the U.S. EPA TSCA Inventory List.

#### **TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

#### **SARA 304 Emergency release notification**

Not regulated.

#### **US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

#### **Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - No  
Pressure Hazard - No  
Reactivity Hazard - No

#### **SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

#### **SARA 313 (TRI reporting)**

Not regulated.

#### **Other federal regulations**

##### **Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

##### **Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**US state regulations** Product is a hazardous substance as defined under the OSHA Hazard Communication Standard and may be reportable under the provisions of SARA Sections 311 and 312.

**US. Massachusetts RTK - Substance List**

SEVERELY HYDROTREATED NAPHTHENIC DISTILLATES (CAS 64742-53-6)

**US. New Jersey Worker and Community Right-to-Know Act**

Not regulated.

**US. Pennsylvania RTK - Hazardous Substances**

Not regulated.

**US. Rhode Island RTK**

Not regulated.

**California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions)**

This product is subject to SCAQMD Rule 1144; it is not compliant and shall not be sold and used in the SCAQMD. The VOC content of the product is 94 g/L, measured by ASTM Method 1868-10. This product has a specified VOC limit of 75 g/L.

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**International Inventories**

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

**16. Other information, including date of preparation or last revision**

**Issue date** 05-12-2014

**Revision date** 12-16-2014

**Version #** 02

**Further information** Not available.

**References** ACGIH

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Information** Product and Company Identification: Physical States  
 Composition / Information on Ingredients: Component Summary  
 Physical & Chemical Properties: Multiple Properties  
 Ecological Information: Ecotoxicity  
 Material Attributes & Uses; Experimental Data: Physical States  
 HazReg Data: North America  
 GHS: Classification