SAFETY DATA SHEET



1. Identification

Product identifier OAK DRAW® 507

STAMPING AND DRAWING FLUID

Other means of identification

SDS number Not applicable

STAMPING AND DRAWING FLUID Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

CIMCOOL® Industrial Products LLC Company name

> 3000 Disney Street Cincinnati, Ohio 45209

Telephone (General

Information)

513-458-8100

Emergency telephone

number

1-800-424-9300 (CHEMTREC)

1-703-527-3887 (CHEMTREC)

Emergency telephone

number (outside USA)

2. Hazard(s) identification

Flammable liquids Category 3 Physical hazards **Health hazards** Acute toxicity, oral Category 4 Aspiration hazard Category 1

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. **Hazard statement**

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Do not eat, drink or smoke

when using this product. Wear protective gloves/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Response

Rinse mouth. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. In

case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: OAK DRAW® 507 SDS US 1/9

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ISOPARAFFINIC HYDROCA	RBON	68551-17-7	60 - 100
TRADE SECRET*		Proprietary*	3 - 7

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell. Under normal

conditions of intended use, this material is not expected to be an inhalation hazard.

Rinse with water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated Skin contact

clothing before reuse.

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical Eye contact

attention if irritation develops and persists.

Rinse mouth thoroughly. Do not induce vomiting. Do not give liquids. If vomiting occurs, keep head Ingestion

low so that stomach content doesn't get into the lungs. Call a physician or poison control center

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause

Most important

symptoms/effects, acute and

temporary irritation. delayed Indication of immediate

medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so

without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the Specific methods

event of fire and/or explosion do not breathe fumes.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: OAK DRAW® 507 2/9

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Type	Value	
ISOPARAFFINIC HYDROCARBON (CAS 68551-17-7)	PEL	500 ppm	
U.S NIOSH			
	Туре	Value	
ISOPARAFFINIC HYDROCARBON (CAS 68551-17-7)	TWA	350 mg/m3	
ACGIH			
	Туре	Value	
ISOPARAFFINIC HYDROCARBON (CAS 68551-17-7)	TWA	100 ppm	

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

recommended.

Skin protection

Hand protectionOtherUse protective gloves made of: Nitrile.Wear suitable protective clothing.

Material name: OAK DRAW® 507

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

9. Physical and chemical properties

CLEAR Appearance Physical state Liquid. **Form** Liquid.

Color Not available. **CHEMICAL** Odor Odor threshold Not available. Not Applicable < 30 °F (< -1.1 °C) Melting point/freezing point > 340 °F (> 171.11 °C) Initial boiling point and boiling

range

127 °F (52.8 °C) Setaflash Flash point

Not available. **Evaporation rate** Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Not available. Vapor pressure Vapor density Not available. Not available. Relative density Insoluble in Water Solubility(ies)

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature**

Viscosity ≤ 20.5 mm²/s @ 40°C 7 cSt @ 100°F (38°C)

Other information

Explosive properties Not explosive. Combustible IIIA Flash point class Not oxidizing. Oxidizing properties

Specific gravity 0.767 98 % VOC ASTM D2369

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Acids. Oxidizing agents.

SDS US Material name: OAK DRAW® 507 4/9 Version #: 01 Issue date: 01-16-2017

Hazardous decomposition

products

Smoke, fumes, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Not classified. Inhalation Not classified. Skin contact Not classified. Eve contact

Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or Ingestion

vomiting may cause a serious chemical pneumonia.

Symptoms related to the

physical, chemical and

toxicological

characteristics

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause

temporary irritation.

Information on toxicological effects

Harmful if swallowed. **Acute toxicity**

Components **Species Test Results**

ISOPARAFFINIC HYDROCARBON (CAS 68551-17-7)

Acute Dermal

Liquid

LD50 Rabbit 15400 mg/kg

Inhalation

Mist

LC50 Rat 12.4 mg/l, 4 hours

Oral Liquid

LD50 Rat 34600 mg/kg

Chronic Inhalation

NOEL Rat > 922 ppm, 6 hours

TRADE SECRET

Acute Oral Liquid

LD50 Rat > 64 mg/kg

64 ml/kg

Skin corrosion/irritation Not classified. Not classified. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not classified.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Material name: OAK DRAW® 507 SDS US

^{*} Estimates for product may be based on additional component data not shown.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated

Not classified.

exposure

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Not classified.

Further information The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Test Results Components

ISOPARAFFINIC HYDROCARBON (CAS 68551-17-7)

Aquatic Acute

Crustacea EC50 Daphnia 1000 mg/l, 48 hours LC50 Rainbow Trout 1000 mg/l, 96 hours Fish

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

TRADE SECRET > 3

No data available. Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1268

Petroleum products, n.o.s. (ISOPARAFFINIC HYDROCARBON) **UN proper shipping name**

Transport hazard class(es)

3 Class Subsidiary risk 3 Label(s) Ш Packing group **Environmental hazards**

> Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 144, B1, IB3, T4, TP1, TP29

Packaging exceptions 150 Packaging non bulk 203

Material name: OAK DRAW® 507 SDS US

^{*} Estimates for product may be based on additional component data not shown.

242 Packaging bulk

Supplemental Information: This material may be transported as "non regulated" by DOT if all criteria referenced in 49 CFR are met and it is in "non-bulk" packages (119 gallons or less).

IATA

UN number UN1268

UN proper shipping name Petroleum products, n.o.s. (ISOPARAFFINIC HYDROCARBON)

Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3 Ш Packing group **Environmental hazards** No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1268

UN proper shipping name PETROLEUM PRODUCTS, N.O.S. (ISOPARAFFINIC HYDROCARBON)

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards**

No Marine pollutant **EmS** F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is not compliant and shall not be sold and used in the SCAQMD. The VOC content of the product is 750 g/L, measured by ASTM Method 1868-10.

This product has a specified VOC limit of 75 g/L.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Material name: OAK DRAW® 507 SDS US

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

01-16-2017 Issue date

Version # 01

Further information Not available. **NFPA** ratings Health: 1 Flammability: 2 Instability: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, **Disclaimer**

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Product and Company Identification: Product and Company Identification **Revision information**

Composition / Information on Ingredients: Ingredients

Transport Information: Proper Shipping Name/Packing Group

Regulatory Information: United States

Material name: OAK DRAW® 507 9/9