

SAFETY DATA SHEET

1. Identification

Product identifier	OAK DRAW® 519 EVAPORATIVE LUBRICANT
Other means of identification	
SDS number	Not applicable
Recommended use	EVAPORATIVE LUBRICANT
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	CIMCOOL® Industrial Products LLC 3000 Disney Street Cincinnati, Ohio 45209
Telephone (General Information)	513-458-8199
Emergency telephone number	1-800-424-9300 (CHEMTREC)
Emergency telephone number (outside USA)	1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Flammable liquid and vapor. May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Vapors may travel considerable distance to a source of ignition and flash back. Ground/bond container and receiving equipment. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.
Response	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash before reuse.
Storage	Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Store away from incompatible materials. Store in accordance with local/regional/national/international regulation.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
C9-C11 ISOALKANES		68551-16-6	60 - 100

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, get medical attention.
Skin contact	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms occur.
Ingestion	Rinse mouth thoroughly. Do not induce vomiting. Do not give liquids. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a POISON CENTER or doctor/physician if you feel unwell.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO ₂). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Vapors may travel considerable distance to a source of ignition and flash back.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment. In the event of fire, wear self-contained breathing apparatus.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Some of these materials, if spilled, may evaporate leaving a flammable residue.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropriate personal protective equipment. Avoid inhalation of vapors or mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Extinguish all flames in the vicinity. Local authorities should be advised if significant spillages cannot be contained. The product is immiscible with water and will spread on the water surface. Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Do not flush spill to drain. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage**Precautions for safe handling**

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Electrostatic Accumulation Hazard: Use proper grounding or bonding procedures. Additional information regarding the safe handling of products with static accumulation potential can be ordered from the American Petroleum Institute (API) request API Recommended Practice 2003 or from the National Fire Protection Association (NFPA) request NFPA 77. Do not ingest. Do not get this material on clothing. Avoid breathing mist or vapor. Avoid contact with skin and eyes. Avoid prolonged and repeated contact. Use only in well-ventilated areas. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Wash contaminated clothing before reuse. Practice good housekeeping. Handle and open container with care. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Do not handle or store near an open flame, heat or other sources of ignition. To maintain product quality, do not store in heat or direct sunlight. Use care in handling/storage. Keep containers closed when not in use. Keep away from food, drink and animal feedingstuffs. Store in original container. Store away from incompatible materials (see Section 10 of the SDS). Store in a well-ventilated place. Room temperature - normal conditions. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection**Occupational exposure limits****U.S. - OSHA**

	Type	Value
C9-C11 ISOALKANES (CAS 68551-16-6)	PEL	500 ppm

U.S. - NIOSH

	Type	Value
C9-C11 ISOALKANES (CAS 68551-16-6)	TWA	350 mg/m ³

ACGIH

	Type	Value
C9-C11 ISOALKANES (CAS 68551-16-6)	TWA	100 ppm

Appropriate engineering controls

Ensure compliance with applicable exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.

Skin protection**Hand protection**

Use protective gloves made of: Nitrile.

Other

Wear suitable protective clothing and gloves.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

CLEAR

Physical state

Liquid.

Form

Liquid.

Color	Not available.
Odor	CHEMICAL
Odor threshold	Not available.
pH	Not Applicable
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 352 °F (> 177.78 °C)
Flash point	118 °F (47.8 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	637 °F (336.11 °C)
Decomposition temperature	Not available.
Viscosity	1.12 cSt @ 38°C
Other information	
Flash point class	Combustible II
Specific gravity	0.76
VOC ASTM D2369	100 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Avoid contact with oxidizers or reducing agents. Strong acids. Strong oxidizing substances.
Hazardous decomposition products	Smoke, fumes, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful. Health injuries are not known or expected under normal use.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin.
---	--

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components	Species	Test Results
C9-C11 ISOALKANES (CAS 68551-16-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	15400 mg/kg
<i>Inhalation</i>		
LC50	Rat	12.4 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	34600 mg/kg
Chronic		
<i>Inhalation</i>		
NOEL	Rat	> 922 ppm, 6 hours

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not classified.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results	
C9-C11 ISOALKANES (CAS 68551-16-6)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	1000 mg/l, 48 hours
Fish	LC50	Rainbow Trout	1000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT	
UN number	UN1268
UN proper shipping name	Petroleum products, n.o.s. (C9-C11 ISOALKANES)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	144, B1, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242
Supplemental Information: This material may be transported as "non regulated" by DOT if all criteria referenced in 49 CFR are met and it is in "non-bulk" packages (119 gallons or less).	

IATA

UN number	UN1268
UN proper shipping name	Petroleum products, n.o.s. (C9-C11 ISOALKANES)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1268
UN proper shipping name	PETROLEUM PRODUCTS, N.O.S. (C9-C11 ISOALKANES)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

Food and Drug Administration (FDA)

Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions)

This product is subject to SCAQMD Rule 1144; it is not compliant and shall not be sold and used in the SCAQMD. The VOC content of the product is 757 g/L, measured by ASTM Method E-1868-10. This product has a specified VOC limit of 50 g/L.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 05-08-2015

Version # 01

Further information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Product and Company Identification
Physical & Chemical Properties: Multiple Properties
Transport Information: Proper Shipping Name/Packing Group
Regulatory Information: United States