SAFETY DATA SHEET



1. Identification

Product identifier OAK KOOL® 638-AF

METALWORKING FLUID

Other means of identification

SDS number Not applicable

Recommended use METALWORKING FLUID

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CIMCOOL® Industrial Products LLC

3000 Disney Street Cincinnati, Ohio 45209

Telephone (General

Information)

513-458-8100

Emergency telephone

number

1-800-424-9300 (CHEMTREC)

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Avoid release to the environment.

Response IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. Take off contaminated clothing and

wash before reuse.

Storage Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Store away

from incompatible materials. Store in accordance with local/regional/national/international

regulation.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

 Material name: OAK KOOL® 638-AF
 SDS US

 Version #: 01
 Issue date: 07-06-2015

 1 / 9

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|---------|
| SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM | | 64742-52-5 | 10 - 30 |
| TRIETHANOLAMINE | | 102-71-6 | 3 - 7 |
| HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S- TRIAZINE | | 4719-04-4 | 1 - 5 |
| MONOETHANOLAMINE | | 141-43-5 | 1 - 5 |
| Other components below reportable lev | els | | 40 - 70 |

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Skin contact Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if symptoms occur.

Rinse mouth thoroughly. Do not induce vomiting. Drink 1 or 2 glasses of water. If vomiting occurs, Ingestion

keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if

you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special Direct contact with eves may cause temporary irritation. Symptoms may include stinging, tearing. redness, swelling, and blurred vision. Skin irritation. Defatting of the skin. May cause allergic skin reaction.

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

treatment needed

General information

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are Suitable extinguishing media

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: OAK KOOL® 638-AF SDS US 2/9

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Prevent product from entering drains. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Do not flush spill to drain. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe dust/fume/gas/mist/vapors/spray. Do not ingest. Do not get this material on clothing. Avoid contact with skin and eyes. Avoid prolonged and repeated contact. Use only in well-ventilated areas. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Wash contaminated clothing before reuse. Practice good housekeeping. Handle and open container with care. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

To maintain product quality, do not store in heat or direct sunlight. Use care in handling/storage. Keep containers closed when not in use. Keep away from food, drink and animal feedingstuffs. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Store in a well-ventilated place. Room temperature - normal conditions. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

| | Type | Value | |
|---|----------------------------|----------|--|
| SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5) | PEL | 5 mg/m3 | |
| US. OSHA Table Z-1 Limits for Air | Contaminants (29 CFR 1910. | 1000) | |
| | Туре | Value | |
| MONOETHANOLAMINE (CAS 141-43-5) | PEL | 6 mg/m3 | |
| , | | 3 ppm | |
| U.S NIOSH | | | |
| | Туре | Value | |
| SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5) | STEL | 10 mg/m3 | |
| , | TWA | 5 mg/m3 | |
| US. NIOSH: Pocket Guide to Chen | nical Hazards | | |
| | Туре | Value | |
| MONOETHANOLAMINE (CAS 141-43-5) | STEL | 15 mg/m3 | |
| | | 6 ppm | |
| | TWA | 8 mg/m3 | |
| | | 3 ppm | |

ACGIH

64742-52-5)

Type Value

SEVERELY-HYDROTREAT TWA 5 mg/m3

ED NAPHTHENIC
PETROLEUM (CAS

US. ACGIH Threshold Limit Values

| | Туре | Value | |
|----------------------|------|---------|--|
| MONOETHANOLAMINE | STEL | 6 ppm | |
| (CAS 141-43-5) | | | |
| TRIETHANOLAMINE (CAS | TWA | 5 mg/m3 | |
| 102-71-6) | | | |
| MONOETHANOLAMINE | TWA | 3 ppm | |
| (CAS 141-43-5) | | | |

Appropriate engineering

controls

Ensure compliance with applicable exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

recommended.

Skin protection

Hand protection Use protective gloves made of: Nitrile.Other Wear suitable protective clothing and gloves.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

9. Physical and chemical properties

Appearance CLEAR
Physical state Liquid.
Form Liquid.
Color Not available.

Odor Chemical
Odor threshold Not available.

pH 10.2

Melting point/freezing point $< 32 \,^{\circ}\text{F} (< 0 \,^{\circ}\text{C})$ Initial boiling point and boiling $> 212 \,^{\circ}\text{F} (> 100 \,^{\circ}\text{C})$

range

Flash point Not Applicable

Evaporation rate Like water when diluted

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Por pressure Not available.

Vapor pressureNot available.Vapor densityNot available.

Not available. Relative density

100 % Water Miscible Solubility(ies)

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperature Not available. Not available. **Decomposition temperature Viscosity** Not available.

Other information

pH in aqueous solution 9.1 @ 5% Specific gravity 1.01 VOC ASTM D2369 12 %

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

Conditions to avoid Contact with incompatible materials.

Acids. Avoid contact with oxidizers or reducing agents. Do not add sodium nitrite or other Incompatible materials

nitrosating agents which may form cancer causing nitrosamines.

Hazardous decomposition

products

Smoke, fumes, oxides of nitrogen, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Health injuries are not known or expected under normal

Skin contact Causes skin irritation. May cause an allergic skin reaction. Frequent or prolonged contact may

defat and dry the skin, leading to discomfort and dermatitis.

Causes serious eye irritation. Eye contact

Ingestion May be harmful if swallowed. Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Defatting of the skin. May cause an allergic

skin reaction.

Information on toxicological effects

May cause an allergic skin reaction. May be harmful if swallowed. Expected to be a low hazard for **Acute toxicity**

usual industrial or commercial handling by trained personnel.

Components **Species Test Results**

MONOETHANOLAMINE (CAS 141-43-5)

Acute

Dermal

LD50 Rabbit 1025 mg/kg

Oral

LD50 Guinea pig 620 mg/kg

> Mouse 700 mg/kg Rat 10.2 g/kg

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat 5.7 mg/l, 4 hours

Material name: OAK KOOL® 638-AF SDS US

| Components | Species | Test Results |
|---------------------|-------------|--------------|
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| TRIETHANOLAMINE (CA | S 102-71-6) | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Oral | | |
| LD50 | Guinea pig | 5300 mg/kg |
| | Rat | 8 g/kg |

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation. Prolonged skin contact may cause temporary irritation. Defatting, drying and

cracking of skin.

Serious eye damage/eye

irritation

Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization May cause an allergic skin reaction. This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be harmful if swallowed and enters airways.

Chronic effects Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components

Species

Test Results

MONOETHANOLAMINE (CAS 141-43-5)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 114 - 196 mg/l, 96 hours

(Oncorhynchus mykiss)

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Aquatic

Acute

Fish LC50 Fish > 100 mg/l, 96 hours

TRIETHANOLAMINE (CAS 102-71-6)

Aquatic

Crustacea EC50 Water flea (Ceriodaphnia dubia) 565.2 - 658.3 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) 10610 - 13010 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

^{*} Estimates for product may be based on additional component data not shown.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

MONOETHANOLAMINE -1.31**TRIETHANOLAMINE** -1

Mobility in soil

This product is miscible in water.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with

chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not established.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S-

TRIAZINE (CAS 4719-04-4)

1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Material name: OAK KOOL® 638-AF SDS US 7/9

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Not regulated. Food and Drug

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. Massachusetts RTK - Substance List

MONOETHANOLAMINE (CAS 141-43-5) TRIETHANOLAMINE (CAS 102-71-6)

US. New Jersey Worker and Community Right-to-Know Act

MONOETHANOLAMINE (CAS 141-43-5) TRIETHANOLAMINE (CAS 102-71-6)

US. Pennsylvania Worker and Community Right-to-Know Law

MONOETHANOLAMINE (CAS 141-43-5) TRIETHANOLAMINE (CAS 102-71-6)

US. Rhode Island RTK

Not regulated.

California South Coast Air **Quality Management District (SCAQMD) Rule** 1144 (VOC Emissions)

This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 83 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 91 % to maintain compliance.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

International Inventories Country(s) or region

| | | on montery or exempt (yearne) |
|-----------------------------|--|-------------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Inventory name

07-06-2015 Issue date

Version # 01

Further information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge.

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: OAK KOOL® 638-AF SDS US

On inventory or exempt (yes/no)*

Revision Information

Product and Company Identification: Product and Company Identification

Hazards Identification: US Hazard Categories Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Transport Information: Proper Shipping Name/Packing Group
Regulatory Information: United States
HazReg Data: North America
GHS: Classification

Material name: OAK KOOL® 638-AF SDS US 9/9