SAFETY DATA SHEET



1. Identification

Product identifier OAK PROTECT@ 2405HF
CORROSION PREVENTIVE

Other means of identification

SDS number Not applicable

Recommended use CORROSION PREVENTIVE

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CIMCOOL® Industrial Products LLC

3000 Disney Street Cincinnati, Ohio 45209

Telephone (General

Information)

513-458-8100

Emergency telephone

number

1-800-424-9300 (CHEMTREC)

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, inhalationCategory 4Serious eye irritationCategory 2

Sensitization, skin Category 1B
Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. May be fatal if swallowed and enters airways. May cause an allergic skin

reaction. Causes serious eye irritation. Harmful if inhaled.

Precautionary statement

Prevention Keep away from flames and hot surfaces-No smoking. Avoid breathing mist or vapor. Wash

thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face

protection.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Wash

contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

75.2% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ALKANES, C12-14-ISO-		68551-19-9	60 - 100
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	10 - 30
ARYLSULFONIC ACID, ALKYL DERIVITIVES, CALCIUM SALTS		93820-57-6	1 - 5
Other components below reportable	levels		5 - 10

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Rinse with water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated

clothing before reuse.

Eve contact Rinse with water. Remove contact lenses, if present and easy to do, Continue rinsing, Get medical

attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Do not induce vomiting. Do not give liquids. If vomiting occurs, keep head

low so that stomach content doesn't get into the lungs. Call a physician or poison control center

temporary irritation. Symptoms may include loss of mobility/consciousness. May cause an allergic

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause

immediately.

skin reaction.

Most important

symptoms/effects, acute and

delaved

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are Suitable extinguishing media

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

media

Do not use water iet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

Combustible liquid. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: OAK PROTECT@ 2405HF SDS US 2/8

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

When using do not smoke. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

Value

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	туре	value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	PEL	5 mg/m3	
ACGIH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM	TWA	5 mg/m3	

Type

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

recommended.

Skin protection

Hand protection Use protective gloves made of: Nitrile. **Other** Wear suitable protective clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance CLEAR Physical state Liquid. **Form** Liquid.

Color Not available. Odor **CHEMICAL** Odor threshold Not available. Ha Not Applicable < 30 °F (< -1.1 °C) Melting point/freezing point

Initial boiling point and boiling

range

> 340 °F (> 171.11 °C)

141 °F (60.6 °C) Setaflash Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Not available. Vapor pressure Vapor density Not available. Not available. Relative density Insoluble in Water Solubility(ies) **Partition coefficient**

(n-octanol/water)

Not available.

Auto-ignition temperature Not available. **Decomposition temperature** Not available.

Viscosity ≤ 20.5 mm²/s @ 40°C 7 cSt @ 100°F (38°C)

Other information

Explosive properties Not explosive. Oxidizing properties Not oxidizing.

0.792 Specific gravity VOC ASTM D2369 73 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Acids. Oxidizing agents.

Hazardous decomposition

products

Smoke, fumes, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact May cause an allergic skin reaction. Eye contact Causes eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and

toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity Harmful if inhaled. May cause an allergic skin reaction.

Components **Test Results Species**

ALKANES, C12-14-ISO- (CAS 68551-19-9)

Acute Dermal Liquid

LD50 Rat > 5000 mg/kg

Oral

Liquid

LD50 Rat > 5000 mg/kg

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

Acute

Dermal Liquid

LD50 Rabbit

> 2000 mg/kg

Inhalation

Mist

LC50 Rat 2.18 mg/l, 4 hr

Oral Liquid

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Not classified.

Serious eye damage/eye

irritation

Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ

toxicity - single exposure

Not classified.

Specific target organ

toxicity - repeated

Not classified.

Aspiration hazard

exposure

May be fatal if swallowed and enters airways.

Chronic effects Not classified.

Material name: OAK PROTECT@ 2405HF

^{*} Estimates for product may be based on additional component data not shown.

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment

possibility that large of frequent spills can have a framiliar of damaging check on the children			
Components	Species	Test Results	
ALKANES, C12-14-ISO- (CA	AS 68551-19-9)		
Aquatic			

Aquatic

Acute

Crustacea EC50 Daphnia > 1000 mg/l, 48 hours Fish LC50 Rainbow trout, donaldson trout > 1000 mg/l, 96 hours

(Oncorhynchus mykiss)

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

Aquatic

Acute

EC50 > 10000 mg/l, 48 hours Crustacea Daphnia Fish LC50 Fish > 100 mg/l, 96 hours

Chronic

Crustacea NOEC 10 mg/l, 21 days Daphnia Fish **NOEC** Fish > 100 mg/l

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. No data available. Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN1268 **UN** number

UN proper shipping name Transport hazard class(es) Petroleum products, n.o.s. (ALKANES, C12-14-ISO-)

Class Combustible Liquid

Subsidiary risk Label(s) 3 **Packing group** Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

144, B1, IB3, T4, TP1, TP29 Special provisions

150 Packaging exceptions 203 Packaging non bulk Packaging bulk 242

Material name: OAK PROTECT@ 2405HF 6/8

^{*} Estimates for product may be based on additional component data not shown.

Supplemental Information: Per 49CFR 173.150 (f)(2) Material classed as a combustible liquid in non-bulk packaging (119 gallons or less) unless listed as a hazardous substance, a hazardous waste, or a marine pollutant, are not subject to any other requirements of this subchapter.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Not established. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

DOT



15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Material name: OAK PROTECT@ 2405HF 7/8

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

US. Pennsylvania Worker and Community Right-to-Know Law

US. Rhode Island RTK

Not regulated.

California South Coast Air **Quality Management** District (SCAQMD) Rule 1144 (VOC Emissions)

This product is subject to SCAQMD Rule 1144; it is not compliant and shall not be sold and used in the SCAQMD. The VOC content of the product is 537 g/L, measured by ASTM Method

E-1868-10. This product has a specified VOC limit of 50 g/L.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

10-20-2016 Issue date

Version # 01

Further information Not available. NFPA ratings Health: 1 Flammability: 2

Instability: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, **Disclaimer**

information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: OAK PROTECT@ 2405HF SDS US