



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** OAKFLO® DSO 5400  
METALWORKING FLUID

**Other means of identification**

**SDS number** Not applicable

**Recommended use** METALWORKING FLUID

**Recommended restrictions** None known.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

**Company name** CIMCOOL® Industrial Products LLC  
3000 Disney Street  
Cincinnati, Ohio 45209

**Telephone (General Information)** 513-458-8100

**Emergency telephone number** 1-800-424-9300 (CHEMTREC)

**Emergency telephone number (outside USA)** 1-703-527-3887 (CHEMTREC)

## 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Serious eye damage/eye irritation Category 2  
Sensitization, skin Category 1  
Reproductive toxicity Effects on or via lactation  
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

**Environmental hazards** Not classified.

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Warning

**Hazard statement** Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause harm to breast-fed children.

**Precautionary statement**

**Prevention** Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact during pregnancy/while nursing. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

**Response** IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse.

**Storage** Store locked up. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Store away from incompatible materials. Store in accordance with local/regional/national/international regulation.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.  
**Supplemental information** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	30 - 60
C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN		63449-39-8	10 - 30
HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S- TRIAZINE		4719-04-4	1 - 5
MONOETHANOLAMINE		141-43-5	1 - 5
TRIETHANOLAMINE		102-71-6	1 - 5
ALKOXYLATED LINEAR ALCOHOLS		68987-81-5	0.5 - 1.5
Other components below reportable levels			10 - 30

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms occur.
<b>Ingestion</b>	Rinse mouth thoroughly. Do not induce vomiting. Do not give liquids. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. May cause allergic skin reaction. May cause respiratory irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
<b>General information</b>	If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Wear suitable protective equipment.
<b>Fire fighting equipment/instructions</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. Move container from fire area if it can be done without risk.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity. Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Do not flush spill to drain. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. Contact local authorities in case of spillage to drain/aquatic environment.

## 7. Handling and storage

### Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not ingest. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material on clothing. Avoid contact during pregnancy/while nursing. Avoid contact with skin and eyes. Avoid prolonged and repeated contact. Use only in well-ventilated areas. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Wash contaminated clothing before reuse. Practice good housekeeping. Handle and open container with care. Do not empty into drains.

### Conditions for safe storage, including any incompatibilities

To maintain product quality, do not store in heat or direct sunlight. Use care in handling/storage. Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. Do not allow material to freeze. Room temperature - normal conditions. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### U.S. - OSHA

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	PEL	5 mg/m <sup>3</sup>

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	Type	Value
MONOETHANOLAMINE (CAS 141-43-5)	PEL	6 mg/m <sup>3</sup> 3 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

	Type	Value
MONOETHANOLAMINE (CAS 141-43-5)	STEL	15 mg/m <sup>3</sup>
	TWA	6 ppm 8 mg/m <sup>3</sup> 3 ppm

**ACGIH**

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	TWA	5 mg/m <sup>3</sup>

**US. ACGIH Threshold Limit Values**

	Type	Value
MONOETHANOLAMINE (CAS 141-43-5)	STEL	6 ppm
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m <sup>3</sup>
MONOETHANOLAMINE (CAS 141-43-5)	TWA	3 ppm

**Appropriate engineering controls**

Ensure compliance with applicable exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.

**Skin protection****Hand protection**

Use protective gloves made of: Nitrile.

**Other**

Wear suitable protective clothing and gloves.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

<b>Appearance</b>	CLEAR
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Not available.
<b>Odor</b>	CHEMICAL
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not Applicable
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not Applicable
<b>Flash point</b>	360 °F (182.2 °C) Cleveland Open Cup
<b>Evaporation rate</b>	Like water when diluted
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.

<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	100 % Water Miscible
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Flash point class</b>	Combustible IIIB
<b>pH in aqueous solution</b>	8.8 @ 5%
<b>Specific gravity</b>	1.006
<b>VOC ASTM D2369</b>	10 %

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Acids. Avoid contact with oxidizers or reducing agents. Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines.
<b>Hazardous decomposition products</b>	Smoke, fumes, oxides of nitrogen, hydrogen chloride, and oxides of carbon

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.
<b>Skin contact</b>	May cause an allergic skin reaction. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May be harmful if swallowed. Expected to be a low ingestion hazard.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. May cause an allergic skin reaction. May cause respiratory irritation.
---	---

### Information on toxicological effects

<b>Acute toxicity</b>	May cause allergic skin reaction. May cause respiratory irritation. May be harmful if swallowed. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.
-----------------------	--

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
9-OCTADECENOIC ACID, 12-HYDROXY-, (9Z,12R)-, HOMOPOLYMER (CAS 27925-02-6)		
<b>Acute</b>		
<i>Oral</i>		
LD50	Rat	> 2000 mg/kg
ALKOXYLATED LINEAR ALCOHOLS (CAS 68987-81-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LD50	Rat	> 50 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	2380 - 2745 mg/kg

Components	Species	Test Results
MONOETHANOLAMINE (CAS 141-43-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	1025 mg/kg
<i>Oral</i>		
LD50	Guinea pig	620 mg/kg
	Mouse	700 mg/kg
	Rat	10.2 g/kg
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
TRIETHANOLAMINE (CAS 102-71-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Oral</i>		
LD50	Guinea pig	5300 mg/kg
	Rat	8 g/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not classified.
<b>Skin sensitization</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
TRIETHANOLAMINE (CAS 102-71-6)	3 Not classifiable as to carcinogenicity to humans.
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not listed.	
<b>Reproductive toxicity</b>	May cause harm to breastfed babies.
<b>Specific target organ toxicity - single exposure</b>	May cause respiratory irritation.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be harmful if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged exposure may cause chronic effects.
<b>Further information</b>	Symptoms may be delayed.

## 12. Ecological information

<b>Ecotoxicity</b>	Contains a substance which causes risk of hazardous effects to the environment.
--------------------	---

Components	Species		Test Results
ALKOXYLATED LINEAR ALCOHOLS (CAS 68987-81-5)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia	1 - 10 mg/l, 48 hours
Fish	LC50	Pimephales promelas	1 - 10 mg/l, 96 hours
C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN (CAS 63449-39-8)			
<b>Aquatic</b>			
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	> 0.1 mg/l, 96 hours
MONOETHANOLAMINE (CAS 141-43-5)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout ( <i>Oncorhynchus mykiss</i> )	114 - 196 mg/l, 96 hours
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia	> 1000 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	> 30000 mg/l, 96 hours
TRIETHANOLAMINE (CAS 102-71-6)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Ceriodaphnia dubia</i> )	565.2 - 658.3 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	10610 - 13010 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

<b>Partition coefficient n-octanol / water (log Kow)</b>	
9-OCTADECENOIC ACID, 12-HYDROXY-, (9Z,12R)-, HOMOPOLYMER	> 12
ALKOXYLATED LINEAR ALCOHOLS	3.01
MONOETHANOLAMINE	-1.31
TRIETHANOLAMINE	-1

**Mobility in soil** This product is miscible in water.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

<b>Disposal instructions</b>	Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

**14. Transport information**

<b>DOT</b>	
<b>UN number</b>	UN3082
<b>UN proper shipping name</b>	Environmentally hazardous substances, liquid, n.o.s. (C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN), MARINE POLLUTANT

**Transport hazard class(es)**

**Class** 9  
**Subsidiary risk** -  
**Label(s)** 9

**Packing group** III

**Environmental hazards**

**Marine pollutant** Yes

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** 8, 146, 335, IB3, T4, TP1, TP29

**Packaging exceptions** 155

**Packaging non bulk** 203

**Packaging bulk** 241

Supplemental Information: 49CFR 171.4 excludes "non-bulk" packages (119 gallons or less) from Marine Pollutant Requirements unless all or part of the shipment is by vessel.

**IATA**

**UN number** UN3082

**UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s. (C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN)

**Transport hazard class(es)**

**Class** 9  
**Subsidiary risk** -

**Packing group** III

**Environmental hazards** Yes

**ERG Code** 9L

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed.

**Cargo aircraft only** Allowed.

**IMDG**

**UN number** UN3082

**UN proper shipping name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN), MARINE POLLUTANT

**Transport hazard class(es)**

**Class** 9  
**Subsidiary risk** -

**Packing group** III

**Environmental hazards**

**Marine pollutant** Yes

**EmS** F-A, S-F

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.


**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**DOT; IATA; IMDG**





## Marine pollutant



### General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S-TRIAZINE (CAS 4719-04-4) 1.0 % One-Time Export Notification only.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - No  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

### US state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

#### US. Massachusetts RTK - Substance List

MONOETHANOLAMINE (CAS 141-43-5)  
TRIETHANOLAMINE (CAS 102-71-6)

#### US. New Jersey Worker and Community Right-to-Know Act

MONOETHANOLAMINE (CAS 141-43-5)  
TRIETHANOLAMINE (CAS 102-71-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

MONOETHANOLAMINE (CAS 141-43-5)

TRIETHANOLAMINE (CAS 102-71-6)

**US. Rhode Island RTK**

Not regulated.

**California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions)**

This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 67 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 100 % to maintain compliance.

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**International Inventories**

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

**16. Other information, including date of preparation or last revision**

**Issue date** 02-19-2015

**Revision date** 07-16-2015

**Version #** 02

**Further information** Not available.

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Information** This document has undergone significant changes and should be reviewed in its entirety.