

1. Identification

Product identifier STARBRIGHT™ 485
METALWORKING FLUID

Other means of identification

SDS number Not applicable

Recommended use METALWORKING FLUID

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Milacron Marketing Company LLC
3000 Disney Street
Cincinnati, Ohio 45209

Telephone (General Information) 513-458-8100

Emergency telephone number 1-800-424-9300 (CHEMTREC)

Emergency telephone number (outside USA) 1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin irritation Category 2
Serious eye irritation Category 2
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information 2.8% of the mixture consists of component(s) of unknown acute oral toxicity. 5.47% of the mixture consists of component(s) of unknown acute dermal toxicity.

The classified hazards shown on this SDS are associated with the product concentrate. These hazards are not expected under recommended use conditions and dilution.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ALKANES C14-16, CHLORO		1372804-76-6	10 - 20
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	10 - 20
HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S- TRIAZINE		4719-04-4	1 - 3
MONOISOPROPANOLAMINE		78-96-6	1 - 3
N-BUTYLETHANOLAMINE		111-75-1	1 - 3
Other components below reportable levels			70 - 80

The exact percentages of hazardous ingredients have been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist. Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Drink 1 or 2 glasses of water. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause an allergic skin reaction.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	PEL	5 mg/m3

U.S. - NIOSH

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	STEL	10 mg/m3
	TWA	5 mg/m3

ACGIH

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	TWA	5 mg/m3

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.

Skin protection

Hand protection

Use protective gloves made of: Nitrile.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	CLEAR
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	CHEMICAL
Odor threshold	Not available.
pH	9.3
Melting point/freezing point	< 24 °F (< -4.4 °C)
Initial boiling point and boiling range	> 212 °F (> 100 °C)
Flash point	Not Applicable
Evaporation rate	Like water when diluted
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	100 % Water Miscible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
pH in aqueous solution	8.8 @ 5%
Specific gravity	1.034
VOC ASTM D2369	9 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines. Acids. Oxidizing agents.
Hazardous decomposition products	Smoke, fumes, oxides of nitrogen, hydrogen chloride, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation	Not classified.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes eye irritation.
Ingestion	Not classified.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
ALKANES C14-16, CHLORO (CAS 1372804-76-6)		
Acute		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	> 2000 mg/kg
Oral		
<i>Liquid</i>		
LD50	Rat	> 5000 mg/kg
MONOISOPROPANOLAMINE (CAS 78-96-6)		
Acute		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	1576 mg/kg
Oral		
<i>Liquid</i>		
LD50	Rat	2813 mg/kg
N-BUTYLETHANOLAMINE (CAS 111-75-1)		
Acute		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	> 2000 mg/kg
Oral		
<i>Liquid</i>		
LD50	Rat	1150 - 7270 mg/kg
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)		
Acute		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
<i>Mist</i>		
LC50	Rat	5.7 mg/l, 4 hours
Oral		
<i>Liquid</i>		
LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes eye irritation.

Respiratory or skin sensitization**Respiratory sensitization** Not a respiratory sensitizer.**Skin sensitization** May cause an allergic skin reaction.**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.**IARC Monographs. Overall Evaluation of Carcinogenicity**

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.**Specific target organ toxicity - single exposure** Not classified.**Specific target organ toxicity - repeated exposure** Not classified.**Aspiration hazard** Not an aspiration hazard.**Chronic effects** Not classified.**Further information** The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.**12. Ecological information****Ecotoxicity** Contains a substance which causes risk of hazardous effects to the environment.

Components		Species	Test Results
ALKANES C14-16, CHLORO (CAS 1372804-76-6)			
Aquatic			
<i>Acute</i>			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	> 0.1 mg/l, 96 hours
MONOISOPROPANOLAMINE (CAS 78-96-6)			
Aquatic			
Fish	LC50	Goldfish (<i>Carassius auratus</i>)	210 mg/l, 96 hours
<i>Acute</i>			
Crustacea	EC50	Daphnia	109 mg/l, 48 hours
N-BUTYLETHANOLAMINE (CAS 111-75-1)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	180 mg/l, 48 hours
Fish	LC50	Ide, silver or golden orfe (<i>Leuciscus idus</i>)	100 mg/l, 96 hours
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)			
Aquatic			
<i>Acute</i>			
Fish	LC50	Fish	> 100 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

MONOISOPROPANOLAMINE	-0.93
N-BUTYLETHANOLAMINE	0.64

Mobility in soil This product is miscible in water.**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN3082
UN proper shipping name	Environmentally hazardous substances, liquid, n.o.s. (ALKANES C14-16, CHLORO), MARINE POLLUTANT
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	8, 146, 335, IB3, T4, TP1, TP29
Packaging exceptions	155
Packaging non bulk	203
Packaging bulk	241
Supplemental Information: 49CFR 171.4 excludes "non-bulk"packages (119 gallons or less) from Marine Pollutant Requirements unless all or part of the shipment is by vessel.	


IATA

UN number	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (ALKANES C14-16, CHLORO)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.


IMDG

UN number	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALKANES C14-16, CHLORO), MARINE POLLUTANT
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

DOT; IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S-
TRIAZINE (CAS 4719-04-4)

1.0 % One-Time Export Notification only.

TSCA Chemical Action Plans, Chemicals of Concern

ALKANES C14-16, CHLORO (CAS 1372804-76-6)

Short-Chain Chlorinated Paraffins (SCCPs) and Other Chlorinated Paraffins Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

MONOISOPROPANOLAMINE (CAS 78-96-6)

Low priority

Food and Drug Administration (FDA) Not regulated.**US state regulations****US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

ALKANES C14-16, CHLORO (CAS 1372804-76-6)

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 56 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 100 % to maintain compliance.**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision**Issue date** 01-29-2015**Revision date** 01-18-2018**Version #** 04**Further information** Not available.**NFPA ratings** Health: 1
Flammability: 0
Instability: 0**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.**Revision information** This document has undergone significant changes and should be reviewed in its entirety.