

CIMSTAR[®] 10-570 HFP



DESCRIPTION

CIMSTAR 10-570 HFP is a chlorine free, oil containing metal working fluid.

APPLICATION

CIMSTAR 10-570 HFP was developed for general machining and grinding applications, such as milling, drilling, turning and grinding operations such as surface, ID and OD. Can be used on ferrous materials, including cast irons, and most aluminum alloys. Do not use on magnesium.

FEATURES & BENEFITS

- Excellent foam control in high pressure applications
- Good on most operations
- Chlorine free

RECOMMENDED STARTING DILUTIONS

CIMSTAR 10-570 HFP is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL[®] Technical Services Specialist.

- Machining and Grinding 5% - 10% (3.6 to 7.2 on the refractometer scale)
- The Refractometer Factor is 1.4
- 5% mix pH is typically 8.7

SAFETY DATA SHEET:

Available at www.cimcool.com

For additional information refer to its OSHA SDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL[®] Technical Services at 1-888-CIMCOOL.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.