



Material Safety Data Sheet

CIMPERIAL® 1073

METALWORKING FLUID CONCENTRATE

DATE EFFECTIVE: 12-12-2011

1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer: CIMCOOL® Industrial Products LLC
3000 Disney Street
Cincinnati, OH 45209 United States

Emergency: Telephone (USA): 1-800-424-9300 (CHEMTREC)
Telephone (Outside USA): 1-703-527-3887 (CHEMTREC)

General Information: Telephone: 1-513-458-8199

Generic Name: Water Soluble Metalworking Fluid Concentrate

2 EMERGENCY INFORMATION

Product is combustible. Product is alkaline. Product is a primary eye irritant. Product may be a primary skin irritant. When using this product on magnesium or alloys of magnesium proper safety procedures must be followed; see Section # 12 Reactivity - Conditions to Avoid. Highway spills could result in slippery conditions. No other significant health effects are associated with this material.

3 POTENTIAL HEALTH EFFECTS OF DIRECT EXPOSURE

	Product	Product at Use Dilution
Inhalation:	Not Applicable	Extended exposure to mist may cause upper respiratory irritation.
Eye Contact:	Product is a primary eye irritant.	Will cause stinging sensation in the eye.
Skin Contact:	Product may be a primary skin irritant.	Not irritating to the skin when used as directed and good personal hygiene is practiced.
Ingestion:	Not orally toxic.	Swallowing small quantities may cause diarrhea, nausea or vomiting.

Medical Conditions generally aggravated by exposure

May aggravate existing skin irritation where further defatting or skin penetration could occur.

Skin irritation (redness and dryness of hands) may be experienced when the diluted product has been contaminated by certain oils, by dissolved metals, or when mix ratio is too strong. When problems occur, use of water-resistant barrier creams may be a temporary control measure. Contact CIMCOOL® Industrial Products LLC Technical Services at 1-513-458-8199 for specific recommendations.

When used in applications generating high levels of mist, operator exposure can be minimized by proper ventilation, use of mist collectors or splash guards, as appropriate. If there is doubt about actual mist levels present, monitoring should be conducted. Contact CIMCOOL® Industrial Products LLC at 1-513-458-8199 for specific recommendations.

Signs and symptoms of exposure**Acute**

Eye injury may result from contact with product. Skin irritation can result from improper use and handling of product.

4 EMERGENCY AND FIRST AID PROCEDURES**Eyes**

In case of eye contact, flush immediately with running water for at least 15 minutes, and get prompt medical attention.

Skin Contact

For skin contact flush with large amounts of water while removing contaminated clothing. Remove contaminated shoes and clothing and launder before reuse. If irritation persists, get medical attention.

Diluted product is not irritating to the skin when used as recommended and good personal hygiene is practiced.

Ingestion

If the material is swallowed, get immediate medical attention or advice. **DO NOT INDUCE VOMITING.** Give two glasses of water or milk. Immediately contact a physician and obtain treatment. Swallowing small quantities of diluted product may cause nausea, diarrhea or abdominal distress.

Inhalation

Inhalation can occur in applications where high mist levels are generated. OSHA has set a PEL of 15 mg/m³ for any airborne particulate as a nuisance level of exposure. NIOSH has set a REL of 0.5 mg/m³ for metalworking fluid mist. If symptoms are experienced, remove source of contamination or move victim to fresh air. If symptoms persist, get medical attention.

5 CONTROL MEASURES**Respiratory protection**

In metalworking fluid applications where time-weighted exposures are 0.5 to 5 mg/m³, mist reduction through improved ventilation, mist collection or process modification is recommended by NIOSH. Where this is not possible, NIOSH recommends the use of any air purifying, half-mask respirator including a disposable respirator, equipped with any P- or R-series particulate filter. If the average exposure will exceed 5 mg/m³, NIOSH recommends use of a powered, air-purifying respirator equipped with a hood or helmet and a HEPA filter. If respiratory problems are present when mist levels are < 0.5 mg/m³, respiratory protection should be based on the individual recommendation of a qualified health care provider.

Caution

The appropriate use and type of respirator is dependent upon use of the product and local operating conditions.

Ventilation

For most applications, adequate shop ventilation is needed. However, when high mist levels are generated or where machines are close together or ventilation is inadequate, operators may experience respiratory irritation. For such applications, use of splash guards or mist collectors is recommended.

Eye protection

Proper metalworking plant eye protection required when handling product concentrate.

Other protective clothing or equipment

Use effective metalworking plant protective clothing as appropriate.

Work / Hygiene Practices

Good personal hygiene should always be followed.

Protective Gloves

Impervious gloves, such as nitrile gloves, are recommended when handling product concentrate.

6 HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

These ingredients may contribute to the acute product hazards listed under the Potential Health Effects section. Other substances, not hazardous under the OSHA Hazard Communication Standard, may be present. Further composition information may be available to health professionals as provided in the Standard.

Component	CAS #	Percent
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES	64742-52-5	30 - 60
SYNTHETIC SODIUM SULFONATE	93820-59-8	1 - 5
TRIISOPROPANOLAMINE	122-20-3	1 - 5
HEXYLENE GLYCOL	107-41-5	1 - 5
ETHOXYLATED LINEAR ALCOHOLS	68920-66-1	1 - 5

7 FIRE AND EXPLOSION HAZARD DATA

Extinguishing Media

Chemical foam, carbon dioxide, or dry chemical

Hazardous Combustion Products

Smoke, fumes, oxides of nitrogen, and oxides of carbon

Flash Point: 315 °F (157.2 °C) Cleveland Open Cup

Lower Explosive Limit: Not Applicable

Upper Explosive Limit: Not Applicable

HMIS RATINGS

Health 1

Flammability Classification 1

Reactivity 0

NFPA RATINGS

Health 1

Flammability Classification 1

Reactivity 0

8 ACCIDENTAL RELEASE MEASURES

Contain the spill, collect on absorbent material, and discard as dictated by Federal, state and local regulations that may apply. Flush area thoroughly with water.

Reportable Quantity: None

9 WASTE DISPOSAL

For Used Product

Disposal procedures must comply with local, county, state and Federal regulations. If pre-treatment is needed, ultrafiltration, emulsion breaking or evaporation may be used. Contact CIMCOOL® Industrial Products LLC at 1-513-458-8199 for assistance.

For Unused Product

Product is not a hazardous waste as defined under 40 CFR 261. Contact CIMCOOL® Industrial Products LLC at 1-513-458-8199 for assistance.

Empty Containers

Empty containers will contain a residue which is not considered a hazardous waste under RCRA regulations. Drums can be drained to a "drip dry" condition by inversion and can be offered for recycling or scrap.

CAUTION: Empty containers retain residue (liquid and/or vapor) and may be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to clean drums since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner. Empty disposable bulk containers should be drained, sealed, and properly discarded. Empty recyclable bulk containers should be drained, sealed, and recycled. Empty pails and jugs should be drained and properly discarded.

10 HANDLING AND STORAGE

Avoid contact of product with eyes or skin. Wash thoroughly after handling. Do not swallow. Do not store product concentrate in direct sunlight or elevated temperatures. Use only as recommended by CIMCOOL® Industrial Products LLC. If frozen, thaw completely at room temperature prior to use.

When using this product on magnesium or alloys of magnesium proper safety procedures must be followed. These include: 1) providing ample flooding of the part with the metalworking fluid, 2) minimizing magnesium chip accumulation in machines, sumps and tanks; 3) promptly separating magnesium chips from the fluid; and 4) providing ventilation for hydrogen gas. For more information, see Section # 12: Reactivity - Conditions to Avoid.

Other Precautions

Product is combustible. Do not heat. Avoid open flames, sparks, and temperatures approaching the flash point. Contains amines. Do not add sodium nitrite or other nitrosating agents to this product because suspected cancer-causing nitrosamines may be formed.

11 PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point:	Not Applicable
Specific Gravity:	0.94
Evaporation Rate:	Like water when diluted
Solubility (H₂O):	100 % Miscible
Volatile Organic Content (by ASTM D2369):	7 %
pH (Concentrate):	Not Applicable
pH (Mix):	8.5 @ 5%
Recommended Starting Dilution:	5 %
Appearance/Odor:	Hazy/Chemical

12 REACTIVITY

Stability

Stable under normal conditions.

Conditions to avoid

Use as directed.

When using this product on magnesium or alloys of magnesium proper safety procedures must be followed. These include: 1) providing ample flooding of the part with the metalworking fluid, 2) minimizing magnesium chip accumulation in machines, sumps and tanks; 3) promptly separating magnesium chips from the fluid; and 4) providing ventilation for hydrogen gas. For more information on machining of magnesium with water based metalworking fluids, please refer to the Hydro Magnesium website, <http://www.hydomagnesium.com>, in their brochure section under Machining Magnesium or the International Magnesium Association Brochure Safe Machining And Handling Of Magnesium Chips, Turnings & Grindings that can be found in their Publication and Video section of their website, <http://www.intlmag.org/index.html>.

Materials to avoid

Avoid contact with strong acids or oxidizers to product.

Hazardous Polymerization

Will not occur.

Combustion Products

Smoke, fumes, oxides of nitrogen, and oxides of carbon

13 TRANSPORTATION INFORMATION

BY LAND

Hazardous Materials Description and Proper Shipping Name (49 CFR 172.101)

Not a Hazardous Material

BY AIR OR VESSEL

Hazardous Materials Description and Proper Shipping Name (49 CFR 172.101)

Not a Hazardous Material

14 REGULATORY INFORMATION

EXPOSURE GUIDELINES

REGULATED MATERIAL	NIOSH REL	OSHA PEL	OSHA STEL	ACGIH TLV	ACGIH STEL
HEXYLENE GLYCOL		25 ppm			
METALWORKING FLUID MIST	0.5 mg/m ³				
MINERAL OIL (MIST)	5 mg/m ³	5 mg/m ³		5 mg/m ³	

CERCLA

No components of this product are present at levels which require reporting under 40 CFR 302.4.

EPCRA (SARA) TITLE III Extremely Hazardous Substances (302): None

HAZARDOUS SUBSTANCES (311/312)

Product is a hazardous substance as defined under the OSHA Hazard Communication Standard and may be reportable under the provisions of SARA Sections 311 and 312.

HAZARD CATEGORIES

Acute Health: Yes

Chronic Health: No

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

RCRA

Product concentrate does not meet the definition of a hazardous waste as defined under 40 CFR 261. It is possible that in use, the product may be contaminated by metals or by chlorinated solvents and the final waste may meet the TCLP definition. Each facility should assess each waste stream to determine if the used fluid should be treated as a hazardous waste.

TSCA

The ingredients of this product are on the TSCA inventory.

STATE RIGHT TO KNOW

Many states have enacted Community Right-To-Know laws which require information beyond that mandated by federal laws. Since some of these laws are inconsistent with the federal laws, the information in this sheet may not fully meet the requirements of every state.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions)

This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 87 g/L, measured by ASTM Method E-1868-10.

This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 86 % to maintain compliance.

TOXIC SUBSTANCES (313)

Component	CAS #	Max % Comments
None		%

GLOSSARY OF ABBREVIATIONS

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds

Disclaimer

NOTE: The opinions expressed herein are those of qualified experts within CIMCOOL® Industrial Products LLC and of their suppliers. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and of these opinions and the condition and use of the product are not within the control of CIMCOOL® Industrial Products LLC , it is the user's obligation to determine the conditions of safe use of the product.