



Product Information Flyer

DESCRIPTION

CIMTECH 310Z metalworking fluid is recommended for machining and grinding operations, including creep feed grinding, on non-ferrous or ferrous metals.

APPLICATION

CIMTECH 310Z can be used on wrought aluminum alloys (2024, 6061, 7050, 7075), cast aluminum alloys (380, 390), cast Iron, nodular iron, carbon steels, stainless steels, titanium and other exotic alloys. It should not be used on magnesium alloys.

For moderate to heavy duty grinding applications such as creep feed. CIMTECH 310Z metalworking fluid is a unique, low pH synthetic fluid designed for the aerospace industry.

FEATURES & BENEFITS

EXCELLENT LUBRICITY:

CIMTECH 310Z provides excellent tool life and surface finish.

EXCELLENT RANCIDITY CONTROL:

Rejects tramp oil, which extends sump life, minimizing the need for additives.

OPERATOR – FRIENDLY:

Provides excellent part visibility - A fresh mix is transparent - No Smoke - Low misting - Mild to the skin.

EXCELLENT FOAM CONTROL:

Very low foaming product, even when used with de-ionized water.

RECOMMENDED STARTING DILUTIONS

CIMTECH 310Z is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL® District Manager.

Grinding	5% - 10%	(1:20 to 1:10)
Machining	5% - 10%	(1:20 to 1:10)

CONCENTRATION

BCG Titration, Total Alkalinity or Refractometer can be used.

The Refractometer Factor is 1.7

Multiply the scale reading obtained on your CIMCOOL® Refractometer by this factor to obtain the mix concentration in percent. Calibrate the refractometer so that it reads 0.0 with water before testing the sample mix. Remove gross contaminants from the sample mixes before testing.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Solubility in water: 100% miscible

Viscosity (SUS) @ 100°F: 110

pH Concentrate: 8.0

Total Chlorine/Chloride, wt%: 0.0/0.08

Silicones: None

Appearance and Odor: Clear/Chemical

Weight, lb/gal, 60°F (15.6 °C): 9.0

Flash Point /Sp.Gr./Boiling Point: SEE MSDS

pH Mix 5%, Typical Operating: 7.8

Total Sulfur, wt%: 0

HANDLING and STORAGE

If frozen, product separates. Thaw completely at room temperature and stir thoroughly before use. Inside storage is recommended.

SAFETY DATA SHEET

Available at www.cimcool.com

For additional information refer to its OSHA MSDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL® Technical Services at 1-513-458-8199.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.