



# Product Information Flyer

## DESCRIPTION

CIMTECH 95 is a synthetic metalworking fluid recommended for light duty grinding operations of ferrous metals.

## APPLICATION

CIMTECH 95 can be used on cast iron, nodular iron, and carbon steels. It should not be used on magnesium alloys or non-ferrous materials.

Designed for high agitation grinding applications such as surface, double disc, and Blanchard grinding.

## FEATURES & BENEFITS

### EXCELLENT FOAM CONTROL:

This product is very low foaming even in turbulent grinding systems.

### EXCELLENT CLEANLINESS:

CIMTECH 95 rejects tramp oil to keep product clean, which extends sump life.

### EXCELLENT RANCIDITY CONTROL:

Excellent fluid life minimizes the need for additives.

### CORROSION PROTECTION:

Excellent rust protection for the work-piece and machine tool.

### RECOMMENDED STARTING DILUTIONS

CIMTECH 95 is to be mixed with water for use. Always add concentrate to water. Fluid may be more difficult to mix when water temperature is below 55°F (13°C). Add no other materials to the concentrate or mix unless approved by your CIMCOOL® Territory Manager.

Grinding	5% - 10%	(1:20 to 1:10)
Machining	5% - 10%	(1:20 to 1:10)

### CONCENTRATION

BCG Titration, Total Alkalinity, CIMCHEK™ Test Strip or Refractometer can be used.

The Refractometer Factor is 4.2

Multiply the scale reading obtained on your CIMCOOL® Refractometer by this factor to obtain the mix concentration in percent. Calibrate the refractometer so that it reads 0.0 with water before testing the sample mix. Remove gross contaminants from the sample mixes before testing. A refractometer is only recommended for use in checking the concentration on a fresh charge.

### TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid

**Solubility in water:** 100% miscible

**Viscosity (SUS) @ 100°F (38°C):** 35

**pH Concentrate:** 9.7

**Total Chlorine/Chloride, wt%:** 0.0/< 1300ppm

**Silicones:** None

**Appearance and Odor:** Clear/Chemical

**Weight, lb/gal, 60°F (15.6°C):** 8.7

**Flash Point /Sp.Gr./Boiling Point:** SEE MSDS

**pH Mix 5%, Typical Operating:** 9.0

**Total Sulfur, wt%:** 0

### HANDLING and STORAGE

If frozen, thaw completely at room temperature. Inside storage is recommended.

### SAFETY DATA SHEET

Available at [www.cimcool.com](http://www.cimcool.com)

For additional information refer to its MSDS, website or contact CIMCOOL® Technical Services at 1-513-458-8199.

***Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.***