

OAK PROTECT[®] 440

CORROSION PREVENTATIVE



Product Information Flyer

DESCRIPTION

OAK PROTECT 440 is a water-based corrosion preventative for ferrous metals.

APPLICATION

OAK PROTECT 440 is intended primarily for use in the protection of ferrous for indoor storage. It is non-staining to the aluminum alloys tested; 7075, 2024 and 3003.

FEATURES & BENEFITS

MEETS THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT VOC STANDARD:

OAK PROTECT 440 is SCAQMD compliant.

BROAD CORROSION INHIBITING CHARACTERISTICS:

OAK PROTECT 440 will provide long-term corrosion protection for indoor storage of ferrous metals. Under optimal conditions, 1 year of protection is expected.

USE AS RECEIVED:

OAK PROTECT 440 is formulated to use as received, which insures that the correct concentration of rust preventative is supplied with each application. Product should be stirred thoroughly prior to use.

EASY TO APPLY:

OAK PROTECT 440 can be best applied by dip method. Brushing or spraying methods can also be used. When practical, dipping is preferred as it assures complete and consistent coverage. The metal surfaces should be thoroughly cleaned and/or deoxidized before applying.

NOTE FOR USE:

For optimal rust prevention during shipment or storage of parts, allow products to dry completely prior to packaging or stacking. Always test the product in advance to confirm that it meets required performance standards for your operations.

RECOMMENDED STARTING DILUTIONS

OAK PROTECT 440 is designed to use as received. Additional dilution is not required. Add no other materials to the concentrate or mix unless approved by your CIMCOOL® District Manager.

Product may separate, mix thoroughly prior to use.

CONCENTRATION

OAK PROTECT 440 is designed to use as received. Additional dilution is not required.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Clear/Chemical

Specific Gravity: 1.0

Solubility in Water: Complete

VOC Content (by METHOD 24): 0%

pH concentrate: 9.0

Silicone: None

HANDLING AND STORAGE

If frozen, product separates. Thaw completely at room temperature and stir prior to use. Inside storage is recommended.

Please stir before use.

SAFETY DATA SHEET

Available at www.cimcool.com

For additional information refer to its OSHA MSDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL® Technical Services at 1-513-458-8199.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.