



# YOUR METALWORKING FLUID SOLUTIONS FOR SOLUTIONS

## OAKWASH<sup>®</sup> DFC 2025 FLOOR CLEANER CONCENTRATE

<b>APPLICATIONS</b>	<p><b>OAKWASH<sup>®</sup> DFC 2025</b> is a liquid, water-based, alkaline floor cleaner and deodorizer. It was developed for use on concrete, linoleum, or ceramic flooring in manufacturing facilities.</p> <p><b>OAKWASH<sup>®</sup> DFC 2025</b> will remove oils, greases, fats, soot, and shop dirt from floors, steps, and walkways. Can be applied by floor scrubbers, spray bottles, mopping, and brushing methods.</p>
<b>FEATURES &amp; BENEFITS</b>	<p><b>EXCELLENT STABILITY IN HARD OR SOFT WATER</b></p> <p><b>HIGH FOAMING FOR ENHANCED DETERGENCY AND EMULSIFICATION</b></p> <p><b>EXCELLENT WETTING PROPETIES-</b> lifts insoluble soils, such as clay, carbon, etc.</p> <p><b>PLEASEANT PINE SCENT</b></p> <p><b>ECONOMICAL-</b> concentrated product can be diluted for low-end use cost.</p> <p><b>NO FLASH POINT</b></p> <p><b>CAN ALSO BE USED AS A MAINTENANCE CLEANER OR DEGREASER</b></p>

<p><b>RECOMMENDED STARTING DILUTIONS</b></p>	<p><b>FOR INDUSTRIAL USE ONLY</b>  <b>Automatic Floor Scrubbers: 3%-5% (1:33 to 1:20)</b>  <b>Light Duty Cleaning: 1%-5% (1:100 to 1:20)</b>  <b>Medium Duty Cleaning: 5%-15% (1:20 to 1:6)</b>  <b>Heavy Duty Cleaning: 10%-25% (1:10 to 1:4)</b></p> <p><b>NOTE:</b> Rinse thoroughly when using manual cleaning methods. <u>Always</u> spot check solution on painted surfaces before applying.</p> <p><b>OAKWASH® DFC 2025</b> is to be mixed with water for use (add concentrate to water)</p> <p>Add no other substances to the concentrate or mix unless approved by Oak Signature Technical Services. Not recommended for use with magnesium or alloyed magnesium.</p>
<p><b>TYPICAL PHYSICAL AND CHEMICAL PROPERTIES</b></p>	<p><b>Physical state:</b> Liquid  <b>Appearance and odor:</b> Clear / Mild pine  <b>Colors available:</b> Undyed  <b>Solubility in water:</b> 100% Miscible  <b>Weight, lb/gal, 60°F (15.6°C):</b> 8.8  <b>Specific gravity, (H<sub>2</sub>O = 1):</b> 1.06  <b>Boiling point, °F (°C):</b> 212 (100)  <b>Flash point, COC, °F (°C):</b> NA  <b>Fire point, COC, °F (°C):</b> NA  <b>Freezing point (or pour point), °F, (°C):</b> 26 (-3)          If frozen, product separates. Thaw completely at room temperature and stir thoroughly.  <b>pH, concentrate:</b> 13.4  <b>pH, 5.0%, typical operating conditions:</b> 12.0  <b>Total chlorine/chloride, wt%, calculated:</b> 0.0/&lt;50 ppm  <b>Total sulfur, wt%, calculated:</b> 0.0  <b>Silicone:</b> None</p>
<p><b>PACKAGING</b></p>	<p>Available in 5-gallon pails, 55-gallon drums, and bulk containers.</p>
<p><b>SAFETY DATA SHEET</b>          Available at <a href="http://www.cimcool.com">www.cimcool.com</a>          For additional information refer to its OSHA MSDS, website or contact your local OAK SIGNATURE SPECIALIST OR DISTRICT MANAGER, or you may contact OAK SIGNATURE® Technical Services at 1-513-458-8199</p> <p><b>Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.</b></p> <p style="text-align: center;">3000 Disney Street          Cincinnati, Ohio 45209          1-513-458-8199 Fax: 1-513-458-817</p> <p style="text-align: right;">PC B20045 8/13/2012</p>	

