



Product Information Flyer

DESCRIPTION

PRODUCTO FC-796 is a heavy duty liquid industrial floor cleaning compound.

APPLICATION

PRODUCTO FC-796 is specifically designed for use in mechanical floor scrubbers. This product will effectively remove grease, oil and shop dirt from concrete, wood block and terrazzo floors. It is not recommended for polished resilient flooring as it will remove many floor waxes.

FEATURES & BENEFITS

VERSATILITY:

PRODUCTO FC-796 is a highly concentrated detergent that can be used in many routine cleaning operations, including floor scrubbing machines as well as mop and bucket operations. Use dilutions can be adjusted depending on the severity of the cleaning job.

PRODUCTO FC-796 is fast drying and will not leave floors slippery after cleaning. It is an alkaline material which does not contain butyl cellosolve. It will emulsify greasy soils and hold them in suspension without re-deposition. This controlled foam product will not clog floor scrubbers and is chemically balanced to prevent corrosion of aluminum scrubber parts.

RECOMMENDED STARTING DILUTIONS

PRODUCTO FC-796 is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL® District Manager.

Mechanical Floor Scrubbers:	2% - 4%	(1:50 to 1:25)
Mop and Bucket:	5%	(1:20)

CONCENTRATION

A Total Alkalinity Procedure, CIMCHEK™ Test Strip or Refractometer can be used to test concentration. A refractometer is only recommended for use in checking the concentration of a fresh charge.

The Refractometer Factor is 5.0

Multiply the scale reading obtained on your CIMCOOL® Refractometer by this factor to obtain the mix concentration in percent. Calibrate the refractometer so that it reads 0.0 with water before testing the sample mix. Remove gross contaminants from the sample mixes before testing.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Solubility in Water: 100% Miscible

Boiling Point: 212°F

pH Concentrate: 12.5

Appearance and Odor: Clear/Chemical

Specific Gravity: 1.07

VOC Content (by ASTM D2369): 8%

pH Mix 4%: 10.3

HANDLING and STORAGE

If frozen, thaw completely at room temperature prior to use. Inside storage is recommended.

SAFETY DATA SHEET

Available at www.cimcool.com

For additional information refer to its OSHA MSDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL® Technical Services at 1-513-458-8199.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.