



PRODUCTO™ SP-330

(formerly CIMCLEAN® MA360)



Parts Cleaner Concentrate

SP-330 is a liquid cleaning compound and corrosion inhibitor designed for use in high-pressure spray washers. It is intended primarily for use in the removal of coolants, machining fluids and honing oils from machined surfaces.

SP-330 is normally used in high-pressure spray washers at ambient temperatures and at a concentration of 3 to 5% by volume and is immediately and completely soluble in cold water. Solutions are heat stable, and will neither break down nor lose corrosion protection properties in washers operated at elevated temperatures.

SP-330 has broad corrosion inhibiting characteristics. It will provide corrosion protection to ferrous and non-ferrous metals. In addition to preventing rust on cast iron and steel, it is extremely effective in the prevention of corrosion and staining on aluminum making it especially well suited for washing aluminum engine blocks, heads and transmission parts and cases. It also prevents corrosion of brass and bronze; both on parts and washer components. SP-330 rejects oil, leading to enhanced washer cleanliness and extended solution life. SP-330 leaves a soft, liquid residue upon evaporation and will not show water spotting after drying.

SP-330 responds readily to conventional waste treatment procedures. It contains no phosphates or silicates. It does not contain EDTA, NTA or related materials. It is not corrosive or combustible and requires only normal care in storage, handling and use.

For additional information concerning SP-330, refer to its OSHA MSDS or contact us at 513-458-8199 for specific recommendations.

TYPICAL PROPERTIES:

Appearance:	Clear
Odor:	Mild, not offensive
pH (Concentrate)	10.4
pH (2%)	8.9
Specific Gravity:	1.10
Density:	9.2 pounds/gallon
Foam Character:	Low

Rev. 6/10 PC-10139

WARRANTY:

Producto Chemicals will grant credit on any product which proves defective in material or workmanship as determined by us subject to the following conditions: all material is subject to our inspection prior to issuing credit; any refund will be adjusted based on the volume of product used; no credit will be granted for used or unused product(s) over one year old as determined by the batch number; no credit will be granted for product placed or stored in a bulk storage tank, mixed with other material or batches in a bulk storage tank or for any material not in original container. The terms in this warranty do not in any way extend to any product thereof covered by this agreement, which has a life, under normal usage, inherently shorter than the one-year period indicated above. Except as set forth expressly in writing herein, there are no other warranties express or implied in respect of any product. No warranty of merchantability or fitness for purpose shall apply.

LIMITATION OF LIABILITY:

Under no circumstances shall we or any affiliate of ours have any liability whatsoever for loss of use or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet



MILACRON MARKETING COMPANY, LLC

CINCINNATI, OHIO 45209

